

Crash-Cart

ArtikelNr. SW/FMV-214-01-001

according to FMVSS 214 and US NCAP

The crash - cart is used to carry out tests according to FMVSS 214 and US NCAP.

Thereby, the crash - cart impacts onto the vehicle with a speed up to 61 km/h collateral under 27°.



	FMVSS 214 / 0°	FMVSS 214 / 27°
length overall	4165 mm	4165 mm
(without honeycomp)	3680 mm	3680 mm
width overall / angle	2245 mm	2455 mm
height overall	850 mm	850 mm
wheel Base / angle	2590 mm	2308 mm
tire tread width / angle	2040 mm	1876 mm
test weight	1361 kg	1361 kg

Adjustable high of the base frame. Aluminum front shield with spindle height adjustment facility, including T-slots to assemble the deformation element (honeycomp). Welded frame construction made of special profile steel tubing (painted surface finish). Pneumatic emergency braking system acting on all wheels. Activation by button (manually, electrically), activation by environment-emergency-stop or activation by trigger-event (impact, gravity-contact). Slewing axles with fixing by 27° and 0°. Retainer for drag gear as specified by the customer.
Optional: camera frame, deformation element (honeycomp)

Calibrated center of gravity	Calibrated moment of inertia
Sx: 1123 ± 25 mm rearward of the front axle	Ix = 508 ± 25 kgm ²
Sy: 7,6±25 mm left of longitudinal centerline	Iy = 2262 ± 133 kgm ²
Sz: 500 ± 25 mm above the ground	Iz = 2572 ± 128 kgm ²

© 2008 Ernst+Co./Aktualisiert: 08.2010

The products shown here comprise additional or special requests by customers that are not within the basic scope of supply. We reserve the right to carry out modifications and improvements at any time without prior notice. The information presented here may be subject to errors.